

MSDS Sheet # 3316

MATERIAL SAFETY DATA SHEET

ISSUE DATE: 02/05

SECTION I

EMERGENCY TELEPHONE NUMBER: 1-800-424-9300 Chemtrec

TELEPHONE NUMBER FOR INFORMATION: 1-818-999-5112

IDENTITY: **LAMINATES DROPS / #3316**

INGREDIENTS/CHEMICAL NAME: Mixture

SECTION II – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS INGREDIENTS AS DEFINED BY OSHA 29 CRF 1910.1200

<u>Chemical Name</u>	<u>Common Name</u>	<u>CAS NO.</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>Other Limits Recommended</u>
Decamethylcyclotetrasiloxane		541-02-6	none established		
Octamethylcyclotetrasiloxane		556-67-2	none established		
Ethanol		64-17-5	1000ppm	1000ppm	

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point (°F)	N/U	Specific Gravity (H2O = 1)	0.91
Vapor Pressure (mm Hg)	N/A	Percent Volatile by Volume	N/A
pH	N/A	Odor	Characteristic
Solubility in Water	Insoluble	Appearance	Clear, colorless, semi-viscous liquid

SECTION IV – FLAMMABILITY AND REACTIVITY

FLASH POINT (METHOD USED): 78°F (CC)	EXPLOSIVE LIMITS	LEL	N/U	UEL	N/U
EXTINGUISHING MEDIA Water spray, foam, dry chemical or CO2 extinguishing agent.					
SPECIAL FIRE FIGHTING PROCEDURES None					
UNUSUAL FIRE HAZARDS None					
STABILITY	UNSTABLE	STABLE	X	CONDITIONS TO AVOID: Heat, fire, sources of ignition.	
INCOMPATIBILITY (Materials to Avoid): Strong oxidizing and reducing agents					
HAZARDOUS DECOMPOSITION/BY PRODUCTS:					

Oxides of Carbon and Nitrogen			
HAZARDOUS POLYMERIZATION	MAY OCCUR	WILL NOT OCCUR X	CONDITIONS TO AVOID: N/A
LAMINATES DROPS / #3316			
Page 2 of 2			

SECTION V – HEALTH AND SAFETY DATA

ROUTES OF ENTRY:	Eye, oral, skin
HEALTH HAZARDS (ACUTE AND CHRONIC):	Avoid eye contact.
SIGNS OF SYMPTOMS OF EXPOSURE:	May cause eye and skin irritation.
MECIDAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:	N/A
EMERGENCY AND FIRST AID PROCEDURES:	If ingested, rinse mouth. Immediately give plenty of water. If appreciable quantities are swallowed, seek medical attention. In case contact with eyes or skin causes irritation, discontinue use and flush with water for 10 minutes. If discomfort persists, seek medical attention.

SECTION VI – PRECAUTIONS FOR SAFE HANDLING AND USE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:	Keep away from heat, sparks and open flame. Store below 50°C (122°F).
OTHER PRECAUTIONS:	Static electricity may accumulate and create a fire hazard. Ground fixed equipment.
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:	Spill will be slippery. Eliminate source of ignition. Use absorbent material to collect. Flush area with hot soapy water. Collect washings for disposal.
WASTER DISPOSAL METHOD:	Use waste disposal methods in compliance with Federal, State and local regulations.

SECTION VII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify Type): None required with normal use.		
VENTILATION	LOCAL EXHAUST None required with normal use.	SPECIAL None
	MECHANICAL (General) Acceptable	OTHER None
EYE PROTECTION: None required with normal use.		
PROTECTIVE GLOVES: None required with normal use. Plastic or rubber for extended exposure.		
OTHER PROTECTIVE EQUIPMENT: None required with normal use.		

SECTION VIII– TRANSPORTATION INFORMATION

DOT Transportation Data (49 CFR 172.101)		
DOT Proper Shipping Name: Flammable liquids, n.o.s.	Hazard Class: 3	
UN Number: UN 1993	Packaging Group: III	

N/A = NOT APPLICABLE
U/N = NOT KNOWN

THE SUBMISSION OF THIS MSDS MAY BE REQUIRED BY LAW, BUT THIS IS NOT AN ASSERTION THAT THE SUBSTANCE IS HAZARDOUS WHEN USED IN ACCORDANCE WITH PROPER SAFETY PROTECTIVES AND NORMAL HANDLING PROCEDURES. DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH.